




## Model: VE-02 Electronic Dosing Pump



### Material of Construction

Sr. No.	Parts	Material
01	Housing	GFPP
02	Liquid Head	PP/PTFE/SS304/SS316
03	NRV	PP/PTFE/SS304/SS316
04	NRV Ball	Ceramic/SS304/SS316
05	Diaphragm	Solid PTFE

### Technical Details

Sr. No.	Model	VE 02
01	Type	Solenoid Operated Electronic Dosing Pump
02	Input Power Supply	230V, 50Hz, 1 Phase
03	Input Power Consumption	40 Watt
04	Flow Adjustment	By Manual Adjustable Speed SPM 0-120
05	Negative Suction	1 mtr
06	End Connection	3/8" Hose Holder
07	Environment Temperature	45°C max.
08	Temperature Of Liquid Handled	50°C max
09	Shipping Weight	3.5 Kg

### Standard Accessories

Sr. No.	Parts	MOC	Quantity
01	Suction & Discharge Piping	LDPE/PTFE	3 meter
02	Foot Valve Cum Strainer	PP	1
03	Antisiphoning valve	PP	1

Pressure in Kg	Capacity in LPH	SPM
1	5.25	120
2	4.55	120
3	4.2	120
4	3.85	120
5	3.5	120
6	3.15	120
7	2.8	120
8	2.75	120